

225

Continuous Duty Electric Diesel Pump

CDP

Diesel Transfer Pump, ideal for use on stationary tanks, fixed fuel transferring systems & dispensers and other similar industrial applications

Lightweight, yet strong non corroding aluminium die cast construction

Self priming vane pump

Continuous Duty Cycle with thermal overload protection

WETTED COMPONENTS Aluminium Nitrile Rubber

Aluminium, Nitrile Rubber, Steel, Nylon

RECOMMENDED USE

Diesel & Kerosene



FLOW RATE	5 VANE PUMP
UPTO 56 LPM	

SPECIFICATIONS

Description	220V AC	
Flow Rate (At Pump Outlet)	Upto 56 LPM*	
Motor	1/2 HP 220V AC, 50/60 Hz	
Rpm	2800	
Internal Bypass Valve	Yes	
Inlet/ Outlet	1" BSP (F)	
Power Cable Length	2m	
Duty Cycle	Continuous Duty	
Horizontal Distance Discharge	50'	
Vertical Distance Discharge	20'	

 $^{{}^*\}mbox{Measured}$ at pump outlet with vehicle engine switched on

ORDERING INFORMATION

CAT NR.	INLET / OUTLET	BOX QTY.
CDP/220UR/EU	1" BSP	1
SPARE PARTS & KITS		
KIT/RPR/CDP	Repair Kit	1

FLUIDS

