

1. General description

Maintains and protects all electrical equipment. Displaces and seals out water and moisture. Prevents corrosion and oxidation. Penetrates and lubricates.

2. Features

- Multi purpose fluid.
- Does not contain silicones.
- Protects metals and alloys.
- Displaces and seals out water and moisture.
- Loosens metal parts seized by dirt, corrosion or dried-up grease.
- Penetrates quickly.
- Safe on all metal surfaces, does not stain.
- Safe on most rubbers, plastics and coatings. Test on sensitive or stressed materials before use.
- Convenient 360° (including inverted position) spray valve for aerosols.
- High purity CO2 propellant, giving an active product content of 95%.

3. Applications

- Electro-mechanical assemblies.
- Control assemblies.
- Electrical aggregates.
- All electrical contacts.
- Printed circuit boards.
- Coin mechanisms.
- Fine mechanics.

4. Directions

- For lubrication and protection: spray a light even coat.
- To remove moisture: spray liberally and allow to drip off.
- When applied by dipping, agitation accelerates the action.
- Test before use on sensitive materials.
- Do not use on energized equipment.
- Do not use on sensitive electronic equipment.
- Allow to dry completely before reactivation.
- To remove residues or excess product, use one of the CRC cleaners.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

5. Typical product data (without propellant)

Appearance	Aerosol	Bulk
Color	Liquid.	Liquid.
	Amber.	Amber.

2-26

Odor	Salicylate.	Salicylate.
Density	0.83 g/cm ³ (@ 20°C).	0.83 g/cm ³ (@ 20°C).
Flash Point	75 °C (Closed Cup)	75 °C (Closed Cup)
Viscosity	4 mPa.s (@ 20°C).	4 mPa.s (@ 20°C).
Density active product	0.89 g/cm ³ (@ 20°C).	0.89 g/cm ³ (@ 20°C).
Operating temperature active product	max 120 °C	max 120 °C
Typical coat weight	2 µm	2 µm

Remarks

Typical corrosion protection results will depend mainly on surface conditions and indoor environment. It may be less than 1 month or more than 6 months. The first application should be checked periodically for signs of corrosion. Once the time of protection under any specific condition is determined, CRC 2-26 may be re-applied at intervals to maintain protection.

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version CRC_GREEN-2_26-20190402
Date 02/04/2019