

SALT GUARD ANTI EFFLORESCENCE PRIME COAT

DESCRIPTION

SALT GUARD is a specially pigmented coating which acts as an anti-efflorescence primer and prevents the growth of salt formation on the wall.

FEATURES

- Excellent alkali & efflorescence resistances
- Physical barrier to water transport
- Chemical barrier to salt migration
- Excellent substrate penetration & top-coat adhesion

BENEFITS

- Long-life high-class appearance of topcoat
- Less topcoat & re-painting required
- Ideal for high-alkaline concrete
- Prevention of top coat defects

TYPICAL APPLICATION

To be applied over concrete, plastered or brick, masonry surfaces.

TYPICAL CHARACTERISTICS

| | |
|---------------------------|-----------------------------------|
| Nature | : single component, liquid |
| Color | : Turbid white |
| Specific gravity at 30 °C | : 1.08 ± 0.04 |
| Inter-coat interval | : 4 to 6 Hrs |
| Dilution | : 50% potable water |
| Coverage | : 55-60 sq. ft. per 2 coats/ ltr. |
| DFT | : 30 40μ |

DIRECTIONS FOR USE

Clean the surface with brush and ensure no loose particle remains on the substrate. On the clean and dry substrate apply it with the help of a brush. Application is to be done till saturation level is achieved. Allow it to dry for 1-2 Hrs. then apply second coat and after 24 hrs apply top coating.

CLEANING OF TOOLS AND EQUIPMENT

Tools and equipment can be easily cleaned with water. If dries, it should be scrapped off.

SALT GUARD ANTI EFFLORESCENCE PRIME COAT

STORAGE AND SHELF LIFE

- In order to preserve all the properties, store the material in the original un-opened containers in cool and dry place.
- Shelf life is 24 months.

PACKING

1 lit 4 ltr and 18 ltr.